






-  **Protection level < 2.5 kV**
-  **SPD based on isolating spark gap technology**
-  **No blow-out vents – no need for safety distances**
-  **Optional contact for remote warning indicator**
-  **Lightning current discharge capability 25 and 60 kA (10/350 μ s)**

Selective ($U_p \leq 2.5$ kV) Surge Protective Device


Product description

With its low protection level, IsoPro230/400Tr-F is a two-stage SPD meeting protection categories B and C in one and the same equipment. For cables up to 10 m long, this makes it possible to renounce on using the normally necessary decoupling elements (ImPro). By using a hermetically sealed high performance isolating spark gap filled with inert gas, it is possible to achieve a high discharge capacity without blow-vent. The first step (valve surge protector) discharges impulse currents (up to 4 kA) without causing follow-on currents in the main. This makes sure that the installation within the building is not endangered by the transients whose energy level is often very low. The fuse will not be strained unnecessarily by follow-on currents in the main. Once the valve surge protector has responded, a residual voltage dependent on the impulse current will build up over the valve

surge protector. As soon as a certain level of impulse current is exceeded (up to 4 kA), this residual voltage will reach the sparkover voltage of the isolating spark gap which in turn will discharge the impulse current thus releasing the valve surge protector. The second step (i.e. the hermetically sealed high performance isolating spark gap filled with inert gas) will take over high energy transients up to 60 kA (10/350 μ s) which do not occur very often, but can happen following direct or very close lightning strikes. The protective circuit is built into an easy to handle snap-on housing designed for 35 mm DIN rail mounting (according to EN 50022) with multi-purpose terminals for wire and busbar connection. Optionally, a potential-free contact (with plug-connector in the housing) for remote warning indication is available.



Dimensions (mm)



IsoPro230/400Tr/25kA-F(/Pk) IsoPro230/400Tr/60kA-F(/Pk)

Technical Data

- Applicaton
- Protection categories B + C lightning SPD for equipotential bonding
 - Single-pole device

Type			IsoPro230/400Tr/25kA-F	IsoPro230/400Tr/60kA-F
Protection category based on E DIN VDE 0675, 6-11/89 and 6-A1-3/96				B + C
Nominal d.c. spark-over voltage	U_{agn}	[V=]		$900 \pm 20\%$
Rated voltage 50/60 Hz	U_N	[V~]		230/400
Max. operating voltage 50/60 Hz	$U_{r,c}$	[V~]		255
Insulation resistance	R_{isol}	[Ω]		$\geq 10^{10}$
Impulse spark-over voltage 1.2/50 μ s	U_{as}	[kV]		≤ 2.5
Protection level	U_p	[kV]		≤ 2.5
Response time	t_A	[ns]		≤ 50
Lightning impulse current 10/350 μ s ($\geq 10x$)	I_{peak}	[kA]	25	60
	Q	[As]	12,5	30
	W/R	[kJ/ Ω]	160	900
Max. permissible line resp. backup fuse		[A]		160 A gL
Short circuit protection with max. 160 AgL fuse		[kA]		25
Operating temperature range	T	[$^{\circ}$ C]		-40 ... +85
Max. connection wire cross-sectional area		[mm 2]		50 rigid or 35 stranded
Recommended connection wire		[mm 2]		50 rigid
Recommended connection torque		[Nm]		4.5
Housing cover / Colour				Polycarbonate (halogen-free) / yellow
Acc. to IEC 529 (1989) protection category				IP 20
Mounting				35 mm rail acc. to EN 50 022

Article number	37 38 25	37 38 30
with potential-free contact	IsoPro230/400Tr/25kA-F/Pk	IsoPro230/400Tr/60kA-F/Pk
Article number	37 38 26	55 05 18

Diagrams

