

The company named below has been authorized by CSA to represent the products listed in this record as "CSA Certified" and to affix the CSA Mark to these products according to the terms and conditions of the CSA Service Agreement and applicable CSA program requirements (including additional Markings).

File No: 015075 0 000

Class No: 5831 01 WIRES Flexible Cord

SUBMITTOR

4544157 Feller GmbH
 Waerndorferstrasse 3
 Giradonifasse 1
 Guenselsdorf, 2525
 Austria

FACTORY

4544157 Feller GmbH
 Waerndorferstrasse 3
 Giradonifasse 1
 Guenselsdorf, 2525
 Austria

September 10, 2003(Replaces:February 26, 2002)

Notes:

1. The jackets on Types St, SVT and SJT may be exposed to oil at 60C.
2. Types SVT, SJT and ST may be shielded.

TO THE REQUIREMENTS OF CSA STANDARD C22.2 NO 49-92 AND CERTIFICATION NOTICE,
 WIRE AND CABLE NO 18:

Type	Max Volt	Size of Conductors (AWG)	No of Conductors	Insul Type	Jacket Type	Notes
● Max temperature rating 60C:						
SPT-1	300	20, 18	2 or 3	PVC	-	2, 4
SPT-2	300	18, 16	2 or 3	PVC	-	2, 4
SPT-1	300	20, 18	2	PVC	PVC	2, 4
SPT-2	300	18, 16	2	PVC	PVC	2, 4

SVT, SVTO	300	18,17,16	2 or 3	PVC	PVC	2, 4, 5
SJT, SJTO	300	18 to 10	2 to 6	PVC	PVC	2, 4, 5
ST, STO	600	18 to 2	2 or more	PVC	PVC	2, 4, 5
SJTW	300	18 to 2	2 or more	PVC	PVC	1, 2, 3
DRT	300	10 to 4	4	PVC	PVC	2, 4, 6

● Max temperature rating 90C:

DRT	300	10 to 4	4	PVC	PVC	2, 4, 6
-----	-----	---------	---	-----	-----	---------

● Max temperature rating 105C:

SPT-1	300	20, 18	2	PVC	PVC	2, 4
SPT-2	300	18, 16	2	PVC	PVC	2, 4
SVT, SVTO	300	18,17,16	2 or 3	PVC	PVC	2, 4, 5
SJT, SJTO	300	18 to 10	2 to 6	PVC	PVC	2, 4, 5
ST, STO	600	18 to 2	2 or more	PVC	PVC	2, 4, 5

Notes:

1. In dark coloured jackets.
2. Flame rating: FT2.
3. Low temperature rating: 40C.
4. In all colours except for clear and translucent.
5. Optional shielding.
6. Types DRT, SVT and SJT also have flame ratings: FT-1, VW-1.

/sp